

TECHNODOLLY 25

► TELESCOPIC CRANES

The TechnoDolly25 is the evolution of the industry standard Technodolly15. The TechnoDolly25 is faster, longer, can be under or overslung with the same level of repeatability of +/-0.2mm. The system can repeat and output the encoded pan, tilt, track, elevation, focus, iris and zoom data to an industry standard format as well as import a (Maya/3ds Max) .fbx file for playback. You can build moves through simple keyframing or standard wheels operating mode. Advanced options include disengaging the pan/tilt motors for a free-form hand held shot or record a push-to-teach tracking shot on the included 60' of track. The TechnoDolly continues to evolve with regular firmware updates, find out how it's perfect for your shoot.



TECHNODOLLY FEATURES

- Quick set-up time
- Extremely versatile, actor driven moco
- Multi-axis repeatability
- Cost efficient (use as standard crane when not in use for moco)
- Small arm with a large shooting area; 24' high, 45' wide, 100' long
- Super quiet operation, ideal for sound
- Very precise, better than +/- 0.2mm

TECHNODOLLY 25 SPECS

Max. lens height	23'9"
Min. length from center to front	6'5"
Max. length from center to front	26"
Max. telescopic travel	18'10"
Length from center to back	7'5"
Min. overall length	13'10"
Max. overall length	33'5"
Door clearance wide	2'7"
Maximum speed	2.4m/s